


**DECLARATION OF PERFORMANCE**

According to Regulation (EU) 305/2011

**N° 0027**

1. Unique identification code of the product-type	<b>La Stubetta 7,5</b>
2. Model and/or batch no. and/or series no. (Article 11-4)	<b>Alpina 4 and 5 levels</b>
3. Intended uses of the product in accordance with the applicable harmonised technical specification	<b>Roomheater burning solid fuel without hot water supply</b>
4. Name or trademark of the manufacturer (Article 11-5)	<b>Cerampiu srl via dell'Artigianato , 19 31011 Asolo (TV)</b>
5. Name and address of the agent (Article 12-2)	-
6. Assessment and verification system for constancy of performance (Annex 5)	<b>System 3</b>
7. Laboratory notified	<b>IMQ Primacontrol (N.B.1881) Via dell'industria, 55 31020 Zoppè S. Vendemmiano (TV)</b>
Test report number (based on System 3)	<b>CPR-16-006</b>
8. Services declare	
<b>HARMONISED TECHNICAL SPECIFICATIONS</b>	<b>EN 13240:2001+A2:2004+AC:2006+A2:2004/AC:2006+A2:2004/AC:2007</b>
<b>ESSENTIAL CHARACTERISTICS</b>	<b>PERFORMANCE</b>
Reaction to fire	<b>A1</b>
Distance to combustible material	<b>Minimum distance from rear: 200 mm Minimum distance from floor: 0 mm Minimum distance from sides: 300 mm</b>
Risk of burning fuel falling out	<b>Pass</b>
Emissions of combustion products Nominal heat output	<b>CO 0,07%</b>
Surface temperature	<b>Pass</b>
Electrical safety	<b>NPD</b>
Cleanability	<b>Pass</b>
Maximum water operating pressure	<b>NPD</b>
Mechanical resistance (to carry a chimney/flue)	<b>NPD</b>
Thermal output Nominal heat output Room heating output	<b>7,5 kW 7,5 kW</b>
Energy efficiency Nominal heat output	<b>η 81,5%</b>
Flue gas temperature Nominal heat output	<b>T 243° C</b>
<p>9. The performance of the product referred to in points 1 and 2 is consistent with the declared performance in point 8. This declaration of performance is issued under the manufacturer's sole responsibility referred to in point 4. Signed in the name and on behalf of the manufacturer by:</p>	
Asolo, 24/02/2020	 (Gazzola Alessandro - Sole Director)